



SELF-ADHESIVE ALUMINUM FOIL TAPE


The aluminum foil tape is flexible and malleable to be adapted to hard-to-reach surfaces such as corners, curvilinear geometries and confined spaces. It is easy to apply and ensures a fast and neat work without the need to prepare the surfaces to be covered and protected. It is resistant to UV degradation, flames, harsh chemicals and moisture. It is light and heat refracting. It has an excellent thermal transmission control (hot/cold).

Specifications and Presentation

Feature	Unit	Value
Adhesion to steel	N/cm	≥ 6,5
Tensile strength	N/cm	≥ 12
Aluminum foil thickness	mm	0,03
Tape thickness	mm	0,06
Dimensions	mm x m	48 x 25 48 x 50

Color Aluminum/Metal

Structure



Applications

Factories, appliances, mean of transport, refrigeration ducts.

Instructions for Use

The surface to be covered shall be free of dust, liquids and oily substances. Apply the tape by pressing down the adhesive side onto the surface to be covered.

Warranty

TACSA warrants this product for one (1) year of storage in its original package. Do not store at temperatures above 30° C.

The provided information is based on experimental results under controlled temperature and humidity conditions, and its repetitiveness depends on external conditions, application methods and tools used. TACSA shall not be held liable for any loss, injury, damage or detriment resulting from an incorrect handling or misuse of the product. Its suitability shall be previously determined for the intended purpose.

www.tacsa.com.ar