



LUBRICANT 15 FOR 1 PLUS

TACSA Lubricant 15 for 1 derives from a mixture of oil by-products, essential oils and high penetration scale removers. It is perfect to protect, lubricate and loosen mechanical parts, remove noise, displace moisture and extend their operating life.

Specifications

Feature	Unit	Value
Density	g/m ³	0,87
Freezing Point	°C	-50
Kinematic Viscosity (40 °C – Ostwald)	Cst	4,500
Flash Point (ASTM D-90 open cup)	°C	96
Boiling Point	°C	>155
Color	Amber	
Scent	Lemmon	
Presentations	Sprays 440 mL/300 g – 216 mL/155 g	

Applications

- It loosens and lubricates rusted parts.
- It removes noise, displaces moisture and protects mechanical parts and metals.
- It is perfect for hinges, locks, drawer runners, chains, bearings, tools, gear assembly, screws, padlocks, pistons, etc.
- It protects against rust and corrosion.
- It displaces moisture in electrical materials, spark plugs and electrical panels.

Precautions: Some rubber types will tend to swell after being exposed to prolonged immersion. Some cleansers and wax coatings may soften. Polycarbonate and transparent polystyrene may weaken or crack after prolonged immersion. It is advisable to test the lubricant on an unexposed surface. KEEP OUT OF CHILDREN'S REACH.

Instructions for Use

Apply directly onto the surface to treat, allow to penetrate and settle for several minutes. Remove the spillover. If the lubricant is meant for corrosion protection, do not remove the product.

Warranty

TACSA warrants this product for 24 months in unopened packages, under fresh and dry storage conditions. Do not expose to high temperatures.

The provided information is based on experimental results under controlled temperature and humidity conditions, and its repetitiveness depends on external conditions, application methods and tools used. TACSA shall not be held liable for any loss, injury, damage or detriment resulting from an incorrect handling or misuse of the product. Its suitability shall be previously determined for the intended purpose.

www.tacsa.com.ar