



CABLE TIES / CABLE TIE MOUNTS

Cable ties injected in polyamide 6.6. Great tensile strength; a pair of scissors, a plier or a utility knife is required to remove them. Their cog ensures a solid fastening. They are easy to apply, so they can be tightened manually or by means of a tool. Due to the variety of sizes, it is possible to adjust them to any type of work, ensuring the highest quality and safety.

Specifications and presentation

Temperature range: -40° C to 85° C

Dimension (mm)	Tightness (kgf)	Ø mín. (mm)	Ø máx. (mm)	Dimension (mm)	Tightness (kgf)	Ø mín. (mm)	Ø máx. (mm)
100 x 2.5	8	3	20.50	350 x 7.6	54	6	98.50
150 x 3.6	18	3	36.00	400 x 4.6 (*)	23	3	113.00
180 x 4.6	23	3	46.00	400 x 7.6	54	6	114.50
200 x 4.6	23	3	49.50	450 x 4.8	23	6	129.00
250 x 4.6	23	3	65.00	450 x 7.6	54	6	130.50
300 x 4.6	23	3	81.00	550 x 4.8	23	3	160.00
300 x 7.6	54	6	82.80	550 x 7.6	54	6	159.00
350 x 4.6	23	3	97.00	610 x 7.6	54	6	181.50
				750 x 7.6	54	6	226.00

Colors: Black. White. * Grey only 400mm x 4.6mm

Applications

- For general and domestic purpose, industries, offices.
- Fastening of cables, conductors, hoses.
- To ensure and separate several materials
- Internal and external use. (Black color UV radiation resistant.)

Instructions for use

The cable tie can be placed without any tools in only one step, introducing the end of the tie through the groove and pulling down until reaching the required length.

Standards

UL E258930 TYPE 21 Certification

The provided information is based on experimental results under controlled temperature and humidity conditions, and its repetitiveness depends on external conditions, application methods and tools used. TACSA shall not be held liable for any loss, injury, damage or detriment resulting from an incorrect handling or misuse of the product. Its suitability shall be previously determined for the intended purpose.

CABLE TIE MOUNTS

Fastening system for cable ties.

Presentation

- 19mm x 19mm
- 28mm x 28mm

Colors

White, Black

Applications

To support cable ties on smooth surfaces.

Warranty

TACSA warrants this product for one (1) year of storage in its original package. Do not store at temperatures above 30° C.