



ANTIFUNGAL NEUTRAL SILICONE SEALANT

It is a single-component neutral silicone sealant, anti-fungal (it prevents fungal growth), suitable for sealing, bonding and insulating a wide variety of materials. It is odorless and does not have any irritating effect. It absorbs vibrations, and it is resistant to weatherability and UV radiation. Electrical insulator. It does not adhere to PE (polyethylene) nor PP (polypropylene). Do not use for structural bonding. Unpaintable.

Specifications and presentation

Feature	Unit	Value
Thickness	g/ml	0,94 -0,95
Dry to the touch	min	5-10
Hardness	shore A	21
Tensile strength	Mpa	> 4
Stretching	%	520
Working temperature	°C	5-40
Presentation		280 ml cartridges
Colors		Clear, White

Applications

- General purpose, due to its high flexibility and elasticity.
- Internal and external use, both under moisture conditions as well as water exposure.
- It can be used as thermal insulator.
- It is suitable to be used on glass, aluminum, ceramic floors, tiles, polycarbonate, fiber cement, PVC, marble and granite.

Instructions for use

Cut the tip of the cartridge, place the applicator spout and mount it on the caulk gun. The substrate surface has to be clean and free of oil and dust. After finishing, remove the silicone residue immediately before film formation takes place.

Since the silicone sealant needs to absorb the air humidity to be cured, it is not suitable for airtight places.

Warranty

TACSA warrants this product for one (1) year of storage in its original package. Do not store at temperatures above 27° C.

The provided information is based on experimental results under controlled temperature and humidity conditions, and its repetitiveness depends on external conditions, application methods and tools used. TACSA shall not be held liable for any loss, injury, damage or detriment resulting from an incorrect handling or misuse of the product. Its suitability shall be previously determined for the intended purpose.

www.tacsa.com.ar