



VINYL ADHESIVE FOR GENERAL PURPOSE

Water-based general-purpose vinyl adhesive, multipurpose. Ideal for gluing stationery, bookbinding, corrugated cardboard, DIY, models, crafts, and general woodworking.

Specifications

Feature	Unit	Value
Viscosity	cP	8.000 - 14.000
Solids	%	>30
Density	g/cm ³	1,13
Odor:		Vinyl
Color:		White
Presentation	Bottles with spout	110 g – 220 g – 500 g – 1 kg
	Bucket	5 kg

Instructions for Use

MIX BEFORE USE

The substrate surface should be clean and dry.
Apply by distributing evenly and join the parts.
Press time 150 min.

Low temperatures or high humidity will increase press time.

Apply thicker layers on highly porous materials.

Store in a cool place in its original container.

Applications

- Multipurpose, suitable for general woodworking
- Joints, gaskets and reinforcement of assemblies
- Craftwork
- Cardboard, paper, leather and fabric

Warranty

TACSA warrants this product for 10-12 months in unopened packages, under fresh and dry storage conditions, and at temperatures between 5 °C-27°C. After that time, it is recommended to homogenize it.
To avoid contamination of unused product, do not return any material to its original content.

The provided information is based on experimental results under controlled temperature and humidity conditions, and its repetitiveness depends on external conditions, application methods and tools used. TACSA shall not be held liable for any

www.tacsa.com.ar