



EXTRA VINYL ADHESIVE

Water based, vinyl adhesive ideal to glue all types of wood, perfect for woodwork and general purpose. It is easy to use and it provides fast and strong bonding. It is suitable to bond joints, gaskets, to assemble and repair furniture, veneering, fiberboard, wood, cardboard, paper, HDF (Chapadur), fabric, expandable polystyrene, to assemble architectural models and craftwork.

Specifications

Feature	Unit	Value
Viscosity (bucket)	cP	12000-15000
Viscosity (bottle)	cP	6000-9000
Solids	%	50
Density	g/cm ³	1,18
Odor:		Vinyl
Color:		White
Presentation	Tins	125g – 250g – 500g – 1kg
	Buckets	6kg – 24kg – 220kg
	Bottles with spout	200g – 800g

Instructions for Use

MIX BEFORE USE

The substrate surface should be clean and dry, free of grease, dust, or any other substance that would prevent proper adherence, penetration and turning the adhesive "wet". Apply with brush, roller, spatula, pasting machine, or notched trowel spreading over the surface uniformly.

Approx. open time: 10 min

Approx. press time: 2 ½ hours.

Low temperatures or high humidity will increase press time.

Apply thicker layers on highly porous materials.

Applications

- General purpose, wood, woodwork.
- Joints, gaskets and reinforcement of assemblies.
- Furniture assembly and repair.
- Craftwork.
- Match boarding and dowels bonding.
- Formica to wood bonding.
- Cardboard, paper, leather and fabric.

Warranty

TACSA warrants this product for 10-12 months in unopened packages, under fresh and dry storage conditions, and at temperatures between 5-27°C. After that time, it is recommended to homogenize the mixture. To avoid contamination of unused product, do not return any material to its original container.

The provided information is based on experimental results under controlled temperature and humidity conditions, and its repetitiveness depends on external conditions, application methods and tools used. TACSA shall not be held liable for any

www.tacsa.com.ar

 MundoTacsa

 TacsArgentina

 TacsArgentina