DATA SHEET



FIBERGLASS ADHESIVE WOVEN TAPE

Self-adhesive woven fiberglass tape with pressure-sensitive adhesive for cement and plasterboard joints.
Our tape is specially designed to prevent cracks and fissures during the curing process between materials with different degrees of expansion or joints where structural movements may occur. Flexible, versatile, and easy to apply.

Specifications and dimensions

Feature	Unit	Value
Thickness	mm	0,2
Basis weight	g/m²	60
Mesh opening	mm	2.85 x 2.85
Application temperature		0°C a 35°C
Dimensions	mm x m	50 x 20 / 50 x 45 / 50 x 90
Color		White

Applications

- Reinforcement and protection of corners.
- Used for both internal and external angles.
- Meeting of plasterboard corners.
- Meeting of partition-partition, partition-wall, partition-slab.

Usage Recommendations

Cut the required length, apply with putty to form the corners.
Press the tape against the corner with putty.
Smooth and clean excess putty. Let dry before sanding and painting.

Warranty

TACSA warrants this product for one (1) year of storage in its original package. Do not store at temperatures above 30°C.

The provided information is based on experimental results under controlled temperature and humidity conditions, and its repetitiveness depends on external conditions, application methods and tools used. TACSA shall not be held liable for any loss, injury, damage or detriment resulting from an incorrect handling or misuse of the product. Its suitability shall be previously determined for the intended purpose.