DATA SHEET



FLEX CORNER TAPE

Microperforated paper tape with aluminum strips for corners, specially designed to create strong and straight angles. It prevents cracks, reinforces, and protects the plaster of the corners. Suitable for angles other than 90 degrees where metal corner beads may not be suitable. Equipped with aluminum strips for easy application, preventing rust and future paint stains. Suitable for both external and internal angles. Features laser-cut micro-perforations for improved adhesion and moisture absorption, reducing the risk of bubbles. Perfect for a professional finish once installed.

Specifications and dimensions

Feature	Unit	Value
Metal strip thickness	mm	0,27
paper basis weight	g/m^2	140 ± 15
Application temperature		0°C to 35°C
Dimensions	mm x m	50 x 30
Color		White

Applications

- Reinforcement and protection of corners.
- Used for both internal and external angles.
- Meeting of plasterboard corners.
- Meeting of partition-partition, partition-wall, partition-slab.

Usage Recommendations

Cut the required length, apply with putty to form the corners.
Press the tape against the corner with putty.
Smooth and clean excess putty. Let dry before sanding and painting.

Warranty

TACSA warrants this product for one (1) year of storage in its original package. Do not store at temperatures above 30°C.

The provided information is based on experimental results under controlled temperature and humidity conditions, and its repetitiveness depends on external conditions, application methods and tools used. TACSA shall not be held liable for any loss, injury, damage or detriment resulting from an incorrect handling or misuse of the product. Its suitability shall be previously determined for the intended purpose.