
DATA SHEET



SELF-EXTINGUISHING NON-ADHESIVE PVC TAPE

Tacsa non-adhesive PVC tape has good dielectric properties and is self-extinguishing. Its composition provides excellent elongation and flexibility, and it is easy to tear. As it has no adhesive, it can be easily removed in case of application errors.

Specifications and presentation

Feature	Unit	Typical value
Dielectric stiffness	kV/mm	≥ 40
Tensile strength	N/cm/mm	≥ 150
Stretching	%	≥125
Working temperature	°C	0 - 90
Flammability	SELF-EXTINGUISHING	
Dimensions (width x length x thickness)	mm x m x mm	19 x 20 x 0,10
Color	Black	
Structure	 PVC FILM	

Applications

,•To protect cables and polyethylene foams.

,•Assembly of cable harness.

,•To cover and protect end fittings.

Instructions for use

Place the tape maintaining a uniform tension, so that it adapts to the surface to be covered.

Warranty

TACSA warrants this product for one (1) year of storage in its original package. Do not store at temperatures above 30° C.

The provided information is based on experimental results under controlled temperature and humidity conditions, and its repetitiveness depends on external conditions, application methods and tools used. TACSA shall not be held liable for any loss, injury, damage or detriment resulting from an incorrect handling or misuse of the product. Its suitability shall be previously determined for the intended purpose.