
# DATA SHEET




## SELF-ADHESIVE PVC REFRIGERATION TAPE

The self-adhesive PVC refrigeration tape is used for coating air conditioning and refrigeration ducts. It grants excellent adhesion, stretching, flexibility, tensile strength and high weatherability properties. It is easy to cut and apply.

### Specifications and presentation

| Feature | Unit | Typical value |
|---|---|---|
| Adhesion to rear side | N/cm | ≥ 1,50 |
| Adhesion to steel | N/cm | ≥ 1,80 |
| Tensile strength | N/cm | ≥17 |
| Stretching | % | ≥ 125 |
| Working temperature | °C | 0 - 90 |
| Thickness | mm | 0,130 ± 0,01 |
| Dimensions | mm x m | 70 x 20 |
| Colors | White, Black, Grey, Brown, Brick-Red | |
| Structure |  | |



### Applications

Coating and protection of air-conditioning and refrigeration ducts.

### Instructions for use

The surface to be repaired shall be free of dust, liquids and oily substances. Apply the tape by pressing down the adhesive side onto the surface.

### Warranty

TACSA warrants this product for one (1) year of storage in its original package. Do not store at temperatures above 30° C.

*The provided information is based on experimental results under controlled temperature and humidity conditions, and its repetitiveness depends on external conditions, application methods and tools used. TACSA shall not be held liable for any loss, injury, damage or detriment resulting from an incorrect handling or misuse of the product. Its suitability shall be previously determined for the intended purpose*